

MELODY INT'L GROUP LTD

Tel: +86-750-3329553 Fax:+86-750-6108609

Website: <http://www.melody-lighting.com/>



Newly TRI-PROOF led light (Standard)

TRI-PROOF Type	Model Number	watts	Additional Model Information	Installed ways	Light Output (lumens)	CCT	CRI	Power Factor	Warranty (years)	Certificate
2FT	TP-2FT-20W	20w	100-277VAC 270° beam angle THD<18 % SDCM≤3 Taiwan SMD2835 IP65	Lifting/ Screw Lifting/ Surface mount	120lm/w	3000K 3500K 4100K 5000K 6000K 6500K	≥82	>0.95	5 years	CE/ROHS EMC UL cUL DLC (Pending)
3FT	TP-3FT-25W	25w								
4FT	TP-4FT-36W	36w								
	TP-4FT-45W	45w								
5FT	TP-5FT-60W	60w								
8FT	TP-8FT-70W	70w								

Newly TRI-PROOF led light (0-10V Dimmable)

TRI-PROOF Type	Model Number	watts	Additional Model Information	Installed ways	Light Output (lumens)	CCT	CRI	Power Factor	Warranty (years)	Certificate
2FT	TP-2FT-20W-DNA	20w	100-277VAC 270° beam angle THD<18 % SDCM≤3 Taiwan SMD2835 IP65 0-10V Dimmable	Suspending Surface mount	120lm/w	3000K 3500K 4100K 5000K 6000K 6500K	≥82	>0.95	5 years	CE/ROHS EMC UL cUL DLC (Pending)
3FT	TP-3FT-25W-DNA	25w								
4FT	TP-4FT-36W-DNA	36w								
	TP-4FT-45W-DNA	45w								
5FT	TP-5FT-60W-DNA	60w								
8FT	TP-8FT-70W-DNA	70w								

Newly TRI-PROOF led light (Microwave motion sensor)

TRI-PROOF Type	Model Number	watts	Additional Model Information	Installed ways	Light Output (lumens)	CCT	CRI	Power Factor	Warranty (years)	Certificate
2FT	TP-2FT-20W-SNA	20w	100-277VAC 270° beam angle THD<18 % SDCM≤3 Taiwan SMD2835 IP65 Microwave motion sensor	Suspending Surface mount	120lm/w	3000K 3500K 4100K 5000K 6000K 6500K	≥82	>0.95	5 years	CE/ROHS EMC UL cUL DLC (Pending)
3FT	TP-3FT-25W-SNA	25w								
4FT	TP-4FT-36W-SNA	36w								
	TP-4FT-45W-SNA	45w								
5FT	TP-5FT-60W-SNA	60w								
8FT	TP-8FT-70W-SNA	70w								

Newly TRI-PROOF led light (Emergency+0-10V Dimmable)

TRI-PROOF Type	Model Number	watts	Additional Model Information	Emergency (Customized)	Installed ways	Light Output (lumens)	CCT	CRI	Warranty (years)	Certificate
2FT	TP-2FT-20W-ENA	20w	100-277VAC 270° beam angle THD<18 % SDCM≤3 PF>0.95 Taiwan SMD2835 IP65 0-10V Dimmable+Emergency	Emergency (6W 3H)	Suspending Surface mount	120lm/w	3000K 3500K 4100K 5000K 6000K 6500K	≥82	5 years	CE/ROHS EMC UL cUL DLC (Pending)
3FT	TP-3FT-25W-ENA	25w								
4FT	TP-4FT-36W-ENA	36w								
	TP-4FT-45W-ENA	45w								
5FT	TP-5FT-60W-ENA	60w								
8FT	TP-8FT-70W-ENA	70w								

Newly TRI-PROOF led light (Emergency+Microwave motion sensor)

TRI-PROOF Type	Model Number	watts	Additional Model Information	Emergency (Customized)	Installed ways	Light Output (lumens)	CCT	CRI	Warranty (years)	Certificate
2FT	TP-2FT-20W-ENA	20w	100-277VAC 270° beam angle THD<18 % SDCM≤3 PF>0.95 Taiwan SMD2835 IP65 Emergency+ Microwave motion sensor	Emergency (6W 3H)	Suspending Surface mount	120lm/w	3000K 3500K 4100K 5000K 6000K 6500K	≥82	5 years	CE/ROHS EMC UL cUL DLC (Pending)
3FT	TP-3FT-25W-ENA	25w								
4FT	TP-4FT-36W-ENA	36w								
	TP-4FT-45W-ENA	45w								
5FT	TP-5FT-60W-ENA	60w								
8FT	TP-8FT-70W-ENA	70w								